Aqua Smart


AQ - 206PC




Features

- Constant Flow between 2 to 4 kg/cm² pressure.
- Flow Rate: 20, 28, 39, 50, 62, 72, 95 LPH.
- Range of operating Pressure:
 20, 28, 39, 50, 62 LPH: 2 4 kg/cm²
 72 and 95 LPH: 1.75 3.5 kg/cm²
- Installed in the ground on stake or hang it by wire.
- Recommended Spacing: 3x3, 3.5x3.5 & 4x4m
- Two Stage wetted diameter control.
- Insect proof design.
- Excellent distribution uniformity.
- Optional trunk protector to protect the plant trunk from wetting, restricting fungus, algea growth.
- Quick thread & push fit adopter connection.
- 4x7mm PE/PVC tube.
- UV & Chemical Resistant material.

Assembly/Exploded View						
Parts	Parts Description	Material				
1	Body	POM				
2	Swivel Grey	FILLED NYLON				
3	Circlip	POM				
4	Nozzle	POM				
5	Nozzle Bottom	POM				
6	Seal	Silicon				
7	Adopter	POM				



Performance Chart								
Nozzle Color	Nozzle Size (mm)	Flow Rate (LPH)	Swivel Color (Grey)		Swivel Color (Black)			
			Short Diameter		Large Diameter			
			Diameter (m)		Diameter (m)			
			1 st Stage	2 nd Stage	1 st Stage	2 nd Stage		
Purple	0.8mm	20	1.2	3.5	1.6	4.5		
Brown	0.94mm	28	1.2	4.0	1.6	5.0		
Green	1.05mm	39	1.4	4.0	2.0	6.0		
Blue	1.15mm	50	1.6	4.5	2.0	6.5		
Yellow	1.25mm	62	1.6	4.6	2.0	7.0		
Orange	1.35mm	72	1.8	4.8	2.0	7.2		
White	1.6mm	95	2.0	5.2	2.2	7.5		





Creating a Green World™

^{*}Tested at 25cm hight above ground

Aqua Smart

AQ - 206PC




Applications

 For Uniform irrigation of orchard, vineyards, nursery & undertree where undulating terrain and long laterel lengths are challenging.



Specially designed Circlip for easy opening of micro sprinkler for cleaning by the end user.







E-mail: contactus@automatworld.com Website: www.automatworld.com Creating a Green World™